XEROX® PRIMELINK® PRINTER

The world's #1* entry production color printer just got even better.



C9065 AND C9070



Xerox® PrimeLink® C9065 and C9070 Printer

The Xerox® PrimeLink® C9065/C9070 delivers the most adaptable capabilities on the market. From superior image quality and unmatched media flexibility to professional-grade finishing, automation and security, it takes entry level to the next level.



IMPROVE YOUR IMAGE

Entry-level price point shouldn't mean entrylevel image quality. With PrimeLink, you can deliver stunning output on every job, every time.

It all starts with resolution. 2400 x 2400 dpi means you get outstanding fine-line detail and text with vivid images and smooth color transitions — even at speeds of up to 70 ppm. EFI servers with embedded PANTONE® technologies such as PANTONE® GOE and PANTONE® PLUS ensure the colors you want are the colors you get.

And a combination of Xerox® Emulsion Aggregation (EA) toner with ultra-low melt technology, +/- 1.2 mm front-to-back registration and Simple Image Quality Adjustment (SIQA) means you get consistent quality from your first print to your last.



^{*} Idealliance, Fogra, and Adobe PDF Print Engine achieved with the optional EFI server

WORK SMARTER, NOT HARDER

Looming deadlines are the norm. Now, there's no reason to compromise. Adding a PrimeLink to your arsenal lets you upgrade your productivity in ways you wouldn't think possible.

Designed to promote multitasking and collaboration, it's customizable to suit your work style. The Xerox® Integrated Color Server comes standard. Or you can choose from one of three optional EFI servers for more capabilities and more volume. All you have to do is select the best fit based on your business applications and the level of automation and color accuracy you need.

The printer also has access to the Xerox App Gallery. With apps that connect to leading applications including Box®, Microsoft® OneDrive®, Google Drive™, Dropbox™ and Microsoft Office 365™, you can print and scan directly to and from the cloud, simplify workflows and automate complex tasks.

Plus, built-in mobile connectivity with @printbyXerox lets your team stay on-task when they're on the go. With this feature, PrimeLink can securely accept print submissions from any email-enabled device — no extra software required.

It's all there with the touch of a button. Say yes to more, and Xerox® PrimeLink C9065/C9070 will help you deliver.

SERVE AND PROTECT

PrimeLink applies a strategic approach to security to keep your network and projects safe from prying eyes. Stop suspicious activity where it starts with our comprehensive approach to security:

- Multiple layers of security include data encryption, access controls, disk overwrite and industry certifications.
- Audit Log ensures an audit trail of operators' key events. These logs are imperative for Administrators/Key Operators to use for troubleshooting, resource optimization and security audits.
- Secure Print holds documents for release until you're ready to retrieve them.
- Secure Scanning includes password protection for PDFs and folders, as well as encryption for scanning to email.

FINISH STRONG

PrimeLink delivers media latitude and finishing options that are best-in-class and unparalleled in an entry-level device.

Print on specialty stocks and heavyweight stocks up to 350 gsm. Print up to 26" (660 mm) with the Extra Long Sheet (XLS) capability up to 220 gsm. And print long runs without refilling the paper tray using high volume feeding options.

Finishing options are professional-grade, easy to navigate and nearly endless. Enjoy options ranging from full-bleed trimmed booklets to punch, crease and fold.



Xerox® PrimeLink® C9065/C9070 Printer

- **1 Two-Tray Oversized High Capacity Feeder:** Adds 4,000 sheets in sizes from 7.2 x 10 in./182 x 250 mm (B5) (up to 350 gsm) to 13 x 26 in./330 x 660 mm (up to 220 gsm).
- 2 Extra Long Sheet (XLS) Capability: Print banners, book jackets, calendars and other applications up to 26 in. (660 mm) long, and up to 220 gsm.
- 3 Control Panel: An intuitive user interface makes it simple to access general print, copy, scan and fax functions, integrated color server, useful apps from the Xerox App Gallery, color controls, security features and much more.
- 4 Integrated Scanner: Single Pass Automatic Document Feeder scans up to 270 impressions per minute; 600 dots per inch color up to 11 x 17/A3. Scan to a variety of output options; desktop, USB, mailbox, FTP, SFTP, NDS, SMB and Job Flow multi-destination scanning.
- 5 Xerox® PrimeLink C9065/C9070 Printer: Prints, copies, scans and faxes all while delivering stunning color image quality at a highly productive 65 ppm color and 70 ppm black-and-white (C9065) or 70 ppm color and 75 ppm black-and-white (C9070).
- **6 Five Internal Trays (Standard):** Includes a 12 x 18 in./SRA3 tray and Tray 5 (Bypass) max weight up to 350 gsm and up to 26 in./ 660 mm sheet size.
- 7 Xerox® Interface Decurler Module: Inline paper cooling and decurler unit improves throughput and efficiency, connecting Production Ready finishing modules, ensuring flat sheets for reliability and speed.

- 8 Xerox Inserter: Insert preprinted or blank media into printed documents with a tray capacity of 250 sheets, sheet sizes up to 13.0 x 19.2 in. (330 x 488 mm) and 350 gsm.
- **9 GBC® AdvancedPunch Pro™:** Lets you create bound documents in-house by combining printing, punching and collating into one convenient step. Choose the punch to fit your needs.
- 10 Xerox® Crease and Two-sided Trimmer: Trims 6-25 mm from the head and foot of prints or booklets to produce an even edge and creases spine. Available on Production Ready Finishers.
- **11 Xerox® C/Z Folder:** Produces Z-fold, C-Fold and Engineering Z-Fold.
- 12 Xerox® Production Ready Finisher Booklet Maker: Ensures consistent high-quality stapled sets for small or large documents with a variable-length stapler, single or dual stapling option and a 100 sheet capacity. Plus, creates stapled booklets up to 30 sheets or 120 imposed pages (uncoated), or 15 sheets or 60 imposed pages (coated).
- 13 Xerox® SquareFold® Trimmer Module: Enhances the power of the Production Ready Finisher with square fold of cover sheets and face trimming to produce booklets.

ADDITIONAL FEEDING AND FINISHING OPTIONS NOT PICTURED

- One-Tray Xerox® High Capacity Feeder Holds 2,000 sheets of 8.5 x 11 in. (A4) paper, 64–220 gsm.
- Banner Feed Guide An option for the Tray 5 (Bypass)/MSI/OHCF that increases reliability when feeding XLS or 350 gsm media.
- One-Tray Oversized High Capacity Feeder with Storage Cabinet — Adds 2,000 sheets in sizes from 4 x 6 in. / 102 x 152 mm (up to 350 gsm) to 13 x 26 in. / 330 x 660 mm (up to 220 gsm).
- Offset Catch Tray 500-sheet stacking.
- Xerox® Business Ready Finisher A lighterduty option for finishing and stacking and staples up to 50 sheets uncoated/15 coated.
- Xerox® Business Ready Booklet Maker Finisher
 Provides booklet making capability.
- Xerox® Production Ready Finisher Produces superior quality finishing and stacking with a 500-sheet top tray and 2,000-sheet stacker tray and built-in bi-directional decurler.
- Xerox® Production Ready Finisher Plus —
 Provides same function as the Production
 Ready Finisher. Used to connect third-party
 inline finishing options.
- Xerox® Basic Punch An option for punching 2/3, 2/4 and Swedish 4-hole on the Production Ready Finisher and Booklet Maker.
- Plockmatic Pro 50/35 Booklet Maker Highest quality production booklets up to 200 pages (up to 50 sheets). Face trimming, square fold, rotate crease and bleed trim.
- Convenience Stapler Staples up to 50 sheets of 20 lb./80 gsm media.

FINISHING APPLICATIONS								
Sort and Collate	XLS	Tri-Fold	Square Fold	Face Trim	Hole Punch			
Booklet	Tabloid Z-Fold	Z-Fold	2-Sided Trim	Basic Punch	Staple			

Xerox® PrimeLink® C9065 and C9070 Printer

DEVICE SPECIFICATIONS	PRIMELINK C9065		PRIMELINK C9070				
SIMPLEX SPEEDS	Color	Black-and-white	Color	Black-and-white			
3.5 x 11 in. / A4	Up to 65 ppm	Up to 70 ppm	Up to 70 ppm	Up to 75 ppm			
1 x 17 in. / A3	Up to 32 ppm	Up to 35 ppm	Up to 35 ppm	Up to 37 ppm			
2 x 18 in. / SRA3	Up to 29 ppm	Up to 30 ppm	Up to 30 ppm	Up to 33 ppm			
UTO DUPLEX SPEEDS	Color	Black-and-white	Color	Black-and-white			
5.5 x 11 in. / A4	Up to 65 ppm 2-sided	Up to 70 ppm 2-sided	Up to 70 ppm 2-sided	Up to 75 ppm 2-sided			
	32 sheets per minute	35 sheets per minute	35 sheets per minute	37 sheets per minute			
11 x 17 in. / A3	Up to 33 ppm 2-sided	Up to 35 ppm 2-sided	Up to 35 ppm 2-sided	Up to 37 ppm 2-sided			
	16 sheets per minute 16 sheets per minute 17 sheets per minute 18 sheets per minute						
Printer Dimensions	Height: 54.8 in. / 1,391.5 mm; Width: 62	in./ 1,574 mm; Depth: 31 in. / 787 m	m				
Monthly Duty Cycle	Up to 300,000 pages (maximum volume capacity expected in any one month, not expected to be sustained on a regular basis)						
Average Monthly Print Volume (AMPV)							
Paper Flexibility/Weights	Standard Paper Capacity: 3,260 sheets (Tray 1 & 2: 500 sheets, Tray 3: 870 sheets, Tray 4: 1,140 sheets, Tray 5 (Bypass): 250 sheets) Max Paper Capacity: 7,260 sheets (Tray 1 & 2: 500 sheets, Tray 3: 870 sheets, Tray 4: 1,140 sheets, Oversized High Capacity Tray 1 & 2: 4,000 sheets) Sizes: Tray 1: 5.5 x 8.5 in. to 12 x 18 in. / A5 to SRA3; Tray 2: 5.5 x 8.5 in. to 11 x 17 in. / A5 to A3; Tray 3: 7.25 x 10.5 in., 8.5 x 11 in. / B5, A4; Max Weight: up to 350 gsm						
Image Quality Print Technology	Benchmark image quality with 2400 x 240	00 dpi resolution with VCSEL ROS and	EA Eco with ultra-low melt technology toner	for a smooth, offset-like finish			
Line Screens			ana grapnics				
Registration Print Features	Advanced registration technology for tighter control Simple Image Quality Adjustment (SIQA) for de-skew, registration and densi - /- 1.2 mm front-to-back registration Print, copy, fax and scan, including Scan to PC, USB or Email, and mobile printing Expansive media range lets you print everything from		 XLS sheet size (Tray 5 and 0 Up to 350 gsm (Tray 5 and auto-duplex up to 256 gsm 	 XLS sheet size (Tray 5 and OHCF) supporting up to 220gsm Up to 350 gsm (Tray 5 and OHCF only), auto-duplex up to 256 gsm (Bypass Tray and OHCF) Xerox® replaceable units for toners, drums, fuser, 			
	postcards to posters, both coated and uncoated stock, up to 350 gsm		·				
	Xerox Extensible Interface Platform® (ΕΙΡ) allows you to		charge corotron, waste bot	charge corotron, waste bottle, staples			
	connect to third-party software solutions		 Custom Paper Setup and Page 	aper Cataloa			
	Inline finishing options offer a professional polish with			Load-while-run toner and paper capability			
	banner printing, stapling, hole-punching, folding and booklet						
	making for presentations, brochures		 Optional Features: Comm 	Optional Features: Common Access Card Enablement Kit, Accounting Options, Foreign Device Interface			
	Be secure with integrated security for IP filtering, image overwrite, secure Scan to Email, authentication and II	eatures such as print, encrypted	Kit, Accounting Options, Fo				
			0 11 1				
Servers	Standard • Xerox® Integrated Color Server		 Xerox® EX-i C9065/C9070 F 	Optional • Xerox® EX-c C9065/C9070 Print Server Powered by Fiery® • Xerox® EX-l C9065/C9070 Print Server Powered by Fiery® • Xerox® EX C9065/C9070 Print Server Powered by Fiery®			
Integrated Scanner	Single-pass Duplex Automatic Document Feeder Color or black-and-white scanner Scan to text searchable PDF, PDF/A, thumbnail preview, XPS®, PCL® 6, HP-Gl (direct submission), TIFF, JPEG 250-sheet capacity		Up to 270 ipm (black-and-vHP-GL2Originals up to 11 x 17 in. (J	 Up to 270 ipm (color, up to 200 gsm) Up to 270 ipm (black-and-white, up to 200 gsm) Originals up to 11 x 17 in. (A3) in weights from 38 gsm (16 lb. bond) to 200 gsm (53 lb. bond) 			
Optional Feeding	High Capacity Feeder (HCF): 2,000 sheets; 7.25 x 10.5 in., 8.5 x 11 in. / 184.2 x 266.7 mm, 279.4 x 215.9 mm (B5, A4); 16 lb. bond to 60 lb. cover / 64 to 220 gsm (uncoated and coated) Optional Oversized High Capacity Feeder (OHCF): One-Tray OHCF: 2,000 sheets plus Storage Cabinet; OHCF: 7.2 x 10 in./182 x 250 mm (B5) (up to 350 gsm) to 13 x 26 in./330 x 660 mm (up to 220 gsm).						
Optional Finishing	Two-Tray OHCF: 4,000 sheets; 4 x 6 in. / 102 x 152 mm (up to 350 gsm) to 13 x 26 in./330 x 660 mm (up to 220 gsm). Business Ready Finisher: Offsetting Top Tray: 500-sheets 8.5 x 11 in. / A4 unstapled. Stacking Stapling Tray: 3,000 sheets unstapled or 100 sets (dual or 4-position staple) 11x17 in., 8.5 x 14 in., A3 or 200 sets (single-position staple) 8.5 x 11 in. / A4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, Stapling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to A3						
	(single position stapling or dual or 4-positic 200 sets (single-position staple) 8.5 x 11 in Other; 5.5 x 8.5 in. / A5 output to top tray; Stacker Tray-16 lb. bond to 110 lb. cover / 6 (coated and uncoated). Booklet Maker-Sax Production Ready Finisher (requires In 146mm to 11.7 x 17"/297 x 432mm. Max* 5.75"/148 x 146mm to 13 x 19.2"/330 x 48 Production Ready Finisher Plus (requirestacker tray. Used to connect third-party Production Ready Finisher with Bookle Trays: 500-sheet top tray, 2,000-sheet st Offset Catch Tray: 500-sheet stacking Xerox® SquareFold® Trimmer Module: Xerox® C/Z Folder: Sheet Size: 8.5 x 11" (Finisher, Booklet Maker. Xerox® Inserter: Capacity: 250 sheets. C Weight: 350 gsm. Compatibility: Producti Max Weight: 350 gsm. Compatibility: Producti Max Weight: 350 gsm. Compatibility: Productive Produc	r Finisher: Offsetting Top Tray: 500 on staple) or 100 stapled sets of 11 x 1. / A4. Sizes: Stacking: 4 x 6 in. to 12 x punch and offset. Paper weights: To 0 to 256 gsm (coated and uncoated) dide-stitch 2 to 16 sheets (7 sheets at terface Decurler Module): Booklet Weight: 350 gsm. Options: Punch, In 18mm. es Interface Decurler Module): Profinitine finishing options. Includes PFI tt Maker (requires Interface Decurler Koklet (7 stray, saddle-stitch booklet tray (unck tray, saddle-stitch booklet tray (unck tray). To 120 pages (30 sheets). Co A4). Half-Z Fold Sheet Size: Larger stray apabilities: Trimming, punching, folson Ready Finisher. In Range: 0.236° (6 mm) to 0.985° (2) duction Ready Finisher and Booklet	17 in. / A3 / SRA3. 11x17 in., 8.5 x 14 in., A3 or 19.2 in. / A6 to SRA3. Stapling; 7.25 x 10.5 in 19.2 in. / A6 to SRA3. Stapling; 7.25 x 10.5 in Pray-16 lb. bond to 110 lb. cover / 60 to 350. Booklet Maker-16 lb. bond to 110 lb. cover / 106 to 176 gsm coated or 5 sheets at 177 to Size: 100 sheets (90 gsm) uncoated, 35 she serter and C/Z Folder. Trays: Two output travides same function as the Production Read Partner Finishing Interface Module. ler Module): Booklet Size: 7.17 x 10.1*/182 x p to 120 pages, 30 sheets/90 gsm uncoatempatibility: Production Ready Finisher, Boocks reducing to 8.5 x 11* (A4). Weight Rangeling, stapling, stacking. Paper Size: 7.2 x 5.8 mm). Paper Size: 7.7 x 8.3*/194 x 210 mm t Maker. Buffering Unit: Up to five customizal	to 11 x 17 in. / B5 to A3.) gsm (coated and uncoated), 60 to 256 gsm 220 gsm coated). ets (90 gsm) coated. Paper Size: 7.2 x 5.7"/182 x yss, 500-sheet top tray, 3,000-sheet stack tray of 5.83 dy Finisher with a 500-sheet top tray and 2,000-sheet x 257mm to 13 x 19.2"/330 x 488mm up to 350 gsm. d, 25 sheets/90 gsm coated). sklet Maker, Crease and Two-Sided Trimmer. ge: 64 - 90 gsm. Compatibility: Production Ready " (182 x 148 mm) to 13 x 19.2" (330 x 488 mm). Max to 13 x 19.2"/330 x 488 mm. ble mountain or valley creases per sheet.			
	Plockmatic Pro 50/35 Booklet Maker: Booklet Capacity: 200 pages (50 sheets). Capabilities: Face trimming, square fold, rotate crease and bleed trim. Paper Size: Up to 12.6 x 9" (320 x 228.6 mm). Max Weight: 300 gsm. Compatibility: Production Ready Finisher Plus. Go to xerox.com/AppGallery to learn how you can expand the capabilities of the PrimeLink C9065/C9070 and work in new ways with dedicated apps for business, education, healthcare and more.						

 $Configurations \ vary \ by \ geographical \ location.$



